



Rocker Switch

Standards, Approvals & Directives

Conforms to BS EN 60669 - 1: 1999 when assembled to appropriate plate and grid and installed correctly.

ASTA Certificate No: 16240

Nemco Certificate No: C15/47987

Description:

Rocker switches are manufactured from brass, aluminium or plastic and finished to complement or match the cover plates. Switches are available as 2-way, intermediate, momentary and 2-way-and-off.

Features:

- Solid Brass/Aluminium rockers
- Two way switches can be wired as one or two way
- All products clearly printed with BS No's, ratings, etc
- 3mm switch contact gap
- Positive switch action

Finishes:

Rocker switch available with our complete range of plate finishes: Unlacquered Brass, Antique Bronze, Stainless Steel, Polished Nickel, Verdigris and Invisible. Steel, Polished Nickel, Verdigris and Invisible.

| Technical Specification | |
|--------------------------------|--|
| Voltage Rating: | 250V AC, 50Hz |
| Current Rating: | 20AX |
| Terminal Capacities: | 4 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 2 x 4mm ² 1 x 6mm ² |
| Operating Temperature: | -5°C to + 40°C |
| IP Rating: | IP2XD |
| Max. Installation Altitude: | 2000 Meters |
| No. of Operations: | 10,000 (20AX Rating) 40,000 (6AX Rating) |

Rocker Switch

